

L Number	Hits	Search Text	DB	Time stamp
1	951	380/30.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:04
2	294	380/29.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:04
3	396	713/156.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:05
4	79	713/158.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:05
5	159	713/167.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:05
6	207	713/181.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:05
7	104	"PKCS #7"	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:06
8	6	"PKCS #7" and "enveloped data"	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:06
9	12	"enveloped data" and "signed data"	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:07
10	16	"enveloped data" and "certificate"	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:07
11	8	"enveloped data" and "content data"	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:07
12	22	"enveloped data" and "encryption"	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:16
13	45006	ibm.asn.	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/08/26 12:16
14	45006	ibm.asn.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/08/26 12:16
15	0	ibm.asn. and "enveloped data"	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/08/26 12:17
16	0	(ibm.asn. and "enveloped data") and "enveloped data"	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/08/26 12:17

17	405	shrader.in.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/08/26 12:17
18	2	shrader.in. and "enveloped data"	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/08/26 12:17


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [more »](#)

[Advanced Search](#)
[Preferences](#)

The "AND" operator is unnecessary -- we include all search terms by default. [\[details\]](#)

Web

Results 1 - 10 of about 1,930 for "**enveloped data**" and "**signed data**" . (0.45 seconds)

Phaos CMS 2.1.1: Interface CMS

... static com.phaos.ASN1.ASN1ObjectID, id_envelopedData The **Enveloped-Data** Content Type ... com.phaos.ASN1.ASN1ObjectID, id_signedData The **Signed-Data** Content Type ...
www.phaos.com/resources/docs/Phaos_CMS_2.1.1/apidoc/com/phaos/cert/cms/CMS.html - 26k -
[Cached](#) - [Similar pages](#)

PKCS7 (X.420:06/1999)

... &Type({PKCS7ContentTable}) } PKCS7-CONTENT-TYPE ::= TYPE-IDENTIFIER PKCS7ContentTable
 PKCS7-CONTENT-TYPE ::= {data | **signed-data** | **enveloped-data** | signed-and ...
www.itu.int/ITU-T/asn1/database/itu-t/x420/1999/PKCS7.html - 30k - [Cached](#) - [Similar pages](#)

Types

... define, R_CM_TYPE_SIGNED_DATA. Indicates the **signed data** type. More... #define,
 R_CM_TYPE_ENVELOPED_DATA_READ. Indicates the **enveloped data** message read type. ...
https://eval.rsasecurity.com.au/downloads/docs/certme/1.5.0/doc/html/group___CM___TYPE.html - 30k -
[Cached](#) - [Similar pages](#)

Cryptographic Message Resource List Definitions

... The full R_CM interface implemented in terms of PKCS #7. Data, **signed data** and **enveloped data** messages are supported. #define R_CM_RES_PKCS7_ENVELOPED_DATA. ...
https://eval.rsasecurity.com.au/downloads/docs/certme/1.5.0/doc/html/group___CM___RL___ITEMS.html - 13k - [Cached](#) - [Similar pages](#)
[\[More results from https://eval.rsasecurity.com.au \]](#)

S [Security]

... signed and **enveloped data** A data content type defined by PKCS #7. This data type ...
signed data A data content type defined by PKCS #7. This data type consists of ...
msdn.microsoft.com/library/en-us/secgloss/security/s_gly.asp - 34k - [Cached](#) - [Similar pages](#)

Example C Program: Encoding an Enveloped, Signed Message [Security ...]

... if(CryptMsgUpdate(hMsg, // handle to the message pbSignedBlob, // pointer to the
signed data BLOB cbSignedBlob, // size of the data BLOB TRUE)) // last call ...
msdn.microsoft.com/.../en-us/seccrypto/security/example_c_program_encoding_an_enveloped_signed_message.asp - 27k - [Cached](#) - [Similar pages](#)
[\[More results from msdn.microsoft.com \]](#)

JCSI S/MIME 3.0: Uses of Class com.dstc.security.cms.CMSException

... supplied data and returns a CMSTypedDataInputStream from which the CMS **signed data**
 can be ... for decryption of one or more instances of CMS **enveloped data** with a ...
www.wedgetail.com/jcsi/smime/apidocs/com/dstc/security/cms/class-use/CMSException.html - 19k -
[Cached](#) - [Similar pages](#)

CryptoSys PKI Toolkit

... You can create and read both **enveloped-data** (encrypted) and **signed-data** Cryptographic
 Message Syntax (CMS) objects, which you can use in S/MIME email messages ...
www.cryptosys.net/pki/ - 14k - [Cached](#) - [Similar pages](#)

Java Technology Forums

... **data** content type provides cryptographic enhancements similar to those resulting

from the sequential combination of **signed-data** and **enveloped-data** content types ...

forum.java.sun.com/thread.jsp?forum=9&thread=540029&tstart=30&frange=15 - 24k - [Cached](#) - [Similar pages](#)

[AW: \[iaik-jce\] PKCS7 enveloped data as an InputStream](#)

... jce] PKCS7 **enveloped data** as an InputStream I'm writing an application that will send possibly large files as **signed data** where the input is **enveloped data**. ...

[jce.iaik.tugraz.at/mailarchive/iaik-jce/msg01489.html](mailto:jce.iaik.tugraz.at@mailarchive/iaik-jce/msg01489.html) - 6k - [Cached](#) - [Similar pages](#)

Google

Result Page: 1 2 3 4 5 6 7 8 9 10 [Next](#)

Free! Get the Google Toolbar. [Download Now](#) - [About Toolbar](#)



[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2004 Google